MARYLIN - MARYLIN CEILING 12 (PL MARY 12) - technical sheet

Lamp base - Description	Power consumption	Lamp type	Light direction
G9	1 x max 60 w	T-4	direct, indirect
Voltage supply	120 V		
Connection	Connect the electrical wires into j-box		
Fixing	Holes fit for installation		
Protection degree	Only dry location		
Ground	Yes		
Switch mode	Switch on/off		
Structure	Mat nickel		
Lampshade material	Lead crystal pendants and mat nickel parts (lead ± 24%)		

MARYLIN CEILING 12
Design by Manuel Vivian

Collection with lead crystal pendants and mat nickel parts. Available in clear or black crystal.

Typology: CEILING

Certifications:



2.2 lb
1.06 ft³

AXO LIGHT USA inc., 22 Shelter Rock Lane - DANBURY, CT 06810, USA - P +1 (203) 730 0452 - F +1 (203) 730 0460 - info@axolightusa.com - www.axolight.it
For further information contact Axo Light USA

Product code composition

CODE	COLOUR	FITTINGS	BULBS
UPMARY12CSNIG9X	crystal	mat nickel	G9 1 x max 60w
UPMARY12NENIG9X	black		

Outer lampshade fabric available colours

CS
crystal

NE
black

UAMARY12 __ NI G9X

NAME _____

NOTES _____

_____

_____

_____

Notes

Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.

AXO LIGHT USA inc., 22 Shelter Rock Lane - DANBURY, CT 06810, USA - P +1 (203) 730 0452 - F +1 (203) 730 0460 - info@axolightusa.com - www.axolight.it
For further information contact Axo Light USA